



Portable diesel transfer pumps

Designed for everyday use in agricultural, construction, automotive & industrial applications

Lightweight, yet strong non-corroding aluminum die-cast construction

Self priming vane pump design

Bypass valve keeps the motor safe even when the outlet is closed

**Duty Cycle**

30 minutes ON / 30 minutes OFF

**Includes Pump with**

- Base plate and lift handle
- Manual Nozzle
- 4m x 3/4" (ID) hose that can be cut & used as suction & delivery hose
- Strainer
- 2m long battery cable with fuse & clamps
- Hardware - 3 hose barbs (3/4") & 4 hose clamps

**WETTED COMPONENTS**

Steel, Aluminum, Zinc, Nylon, NBR, PVC Nitrile, Acetal


**RECOMMENDED USE**

Diesel & Kerosene




**FLOW RATE**

UPTO 46 LPM



**FLUIDS**

**DIESEL**      **KEROSENE**



**SPECIFICATIONS**

	12V DC	24 V DC
MOTOR	1/4 HP 12V DC	1/4 HP 24V DC
RPM	2600	2600
AMP	18 Amp	11 Amp
INTERNAL BYPASS VALVE	Yes	Yes
OUTLET	3/4" NPT	3/4" NPT
BATTERY CABLE (2 WIRE)	2m	2m

**ORDERING INFORMATION**

CAT NR.	DESCRIPTION	BOX QTY.
EDP/12M/ST	12V DC	1
EDP/24M/ST	24V DC	1

**WARNING**

Do not use with flash point below 38°C such as Petrol or Alcohol. Sparking could result in explosion causing fatal injury